

BBCV2.MH46916 - Lithium Batteries - Component

Lithium Batteries - Component

See General Information for Lithium Batteries - Component**KAYO INDUSTRIAL CO LTD**

FL 4-5 11 BLDG HUALIAN INDUSTRIAL
 PARK HUANING RD DALANG COMMUNITY
 DALANG ST BAOAN DISTRICT
 SHENZHEN, GUANGDONG 518000 CHINA

MH46916

Model No.	Secondary Type ^[d]	Max Charging Current (I _c), mA	Max Charging Voltage, V dc ^[e]	Test Compliance ^[f]
053048	Lithium ion (Prismatic)	800	4.2	3, 4
063450	Lithium ion (Prismatic)	1200	4.6	1
083442	Lithium ion (Pouch)	1070	4.2	1
10110	Lithium ion (Pouch)	65	4.2	1
103048	Lithium ion (Pouch)	1500	4.2	2
103443	Lithium ion (Pouch)	1500	4.6	1
103450	Lithium ion (Prismatic)	1700	4.6	1
222530	Lithium ion	120	4.2	1
251520	Lithium ion	40	4.2	1
254060	Lithium ion (Pouch)	500	4.2	1
254486	Lithium ion	800	4.2	1
283234	Lithium ion	210	4.2	1
283436	Lithium ion	300	4.2	1
2867120	Lithium ion (Pouch)	2500	4.2	1
321028	Lithium ion (Pouch)	55	4.2	1
323436	Lithium ion	350	4.2	1
3269131	Lithium ion (Pouch)	3400	4.3	1
334862	Lithium ion	1000	4.2	4
352535	Lithium ion	260	4.2	1
3551118	Lithium ion	2500	4.2	4
356066	Lithium ion	1250	4.2	1
371427	Lithium ion	100	4.2	1

384455	Lithium ion (Prismatic)	900	4.2	4
384461	Lithium ion (Prismatic)	1000	4.2	4
3997132	Lithium ion	5900	4.2	1
401020	Lithium ion (Pouch)	55	4.2	1
401220	Lithium ion	60	4.2	1
401230	Lithium ion	100	4.2	1
401838	Lithium ion (Pouch)	240	4.2	1
402827	Lithium ion (Pouch)	135	4.2	1
403641	Lithium ion	550	4.2	1
423450	Lithium ion (Prismatic)	850	4.2	3, 4
423465	Lithium ion	1000	4.2	4
424795	Lithium ion	2200	4.2	1
425068	Lithium ion	1600	4.2	4
4277112	Lithium ion (Pouch)	3750	4.2	1
438384	Lithium ion (Pouch)	3000	4.2	1
451834	Lithium ion	230	4.5	1
452425	Lithium ion	200	4.2	1
453048	Lithium ion (Pouch)	360	4.2	1
454261	Lithium ion (Pouch)	750	4.2	1
484461	Lithium ion (Prismatic)	1450	4.6	1
501630	Lithium ion	200	4.2	1
502248	Lithium ion (Pouch)	500	4.2	1
503030	Lithium ion (Pouch)	400	4.2	1
503450	Lithium ion	850	4.5	4
505067	Lithium ion	1850	4.5	2, 4
505068	Lithium ion	1800	4.2	1
523436	Lithium ion (Prismatic)	650	4.2	3, 4
523450A	Lithium ion (Prismatic)	1000	4.2	3, 4
523450B	Lithium ion (Prismatic)	1100	4.6	1
525085	Lithium ion (Pouch)	2600	4.2	1
534863	Lithium ion	1900	4.2	1
543450	Lithium ion	1000	4.2	4
551228	Lithium ion (Pouch)	120	4.2	1

551730	Lithium ion (Pouch)	125	4.2	1
553038	Lithium ion	560	4.2	1
553248	Lithium ion	900	4.2	1
553446	Lithium ion (Prismatic)	1000	4.6	1
553446AR	Lithium ion (Prismatic)	1000	4.2	2
554065	Lithium ion (Pouch)	1700	4.2	1
582535	Lithium ion (Pouch)	450	4.2	1
595377	Lithium ion (Pouch)	3300	4.6	1
602025	Lithium ion	250	4.5	4
602129	Lithium ion (Pouch)	400	4.2	1
602535	Lithium ion (Pouch)	250	4.2	1
602937	Lithium ion	600	4.2	1
603038	Lithium ion	700	4.2	1
606080	Lithium ion (Pouch)	2000	4.35	1
6085100	Lithium ion (Pouch)	3000	4.2	1
623348	Lithium ion (Pouch)	1200	4.2	1
623450	Lithium ion (Pouch)	1300	4.35	1
628080	Lithium ion (Pouch)	2250	4.2	1
632560	Lithium ion (Pouch)	475	4.2	1
643750	Lithium ion (Prismatic)	1350	4.2	4
652339	Lithium ion (Pouch)	275	4.2	1
652631	Lithium ion	500	4.2	1
654764	Lithium ion	2000	4.2	4
655097	Lithium ion	4000	4.2	4
672139	Lithium ion (Pouch)	500	4.2	1
683566	Lithium ion (Pouch)	940	4.2	1
702990	Lithium ion (Pouch)	1000	4.2	1
722240	Lithium ion	630	4.2	1
723759	Lithium ion (Prismatic)	1800	4.6	1
802030	Lithium ion	420	4.2	1
803448	Lithium ion (Pouch)	700	4.2	1
803465	Lithium ion	2000	4.2	1
855793	Lithium ion (Pouch)	3000	4.2	1

875880	Lithium ion (Pouch)	1850	4.2	1
882940	Lithium ion	1000	4.2	4
9040120	Lithium ion (Pouch)	2750	4.2	1
9675135	Lithium ion	10000	4.2	2
ICR14430-650	Lithium ion (Cylindrical)	1100	4.3	2, 3
ICR14500 700	Lithium ion (Cylindrical)	700	4.3	2, 3
ICR14500 800	Lithium ion (Cylindrical)	800	4.3	2, 3
ICR14500-500	Lithium ion (Cylindrical)	400	3.8	3
ICR14650-1100	Lithium ion (Cylindrical)	1100	4.3	2, 3
ICR17335-400	Lithium ion (Cylindrical)	400	3.8	1
ICR18650	Lithium ion (Cylindrical)	1500	4.35	1
ICR18650-1100	Lithium ion (Cylindrical)	1100	3.8	3
ICR18650-1300	Lithium ion (Cylindrical)	1300	3.8	3
ICR18650-1400	Lithium ion (Cylindrical)	1400	4.3	2, 3
ICR18650-1800	Lithium ion (Cylindrical)	1800	4.3	2, 3
ICR18650-2000	Lithium ion (Cylindrical)	2000	4.3	2, 3
ICR18650-2200	Lithium ion (Cylindrical)	2200	4.3	2, 3
ICR18650-2400	Lithium ion (Cylindrical)	2400	4.3	2, 3
ICR18650-2600	Lithium ion (Cylindrical)	2600	4.2	1
ICR21750-3200	Lithium ion (Cylindrical)	3200	4.2	3
ICR26650-2400	Lithium ion (Cylindrical)	2400	3.8	3
ICR26650-2800	Lithium ion (Cylindrical)	2800	3.8	3
ICR32650-3800	Lithium ion (Cylindrical)	3800	3.8	3
ICR32650-4000	Lithium ion (Cylindrical)	4000	3.8	3
KPL476089	Lithium ion (Pouch)	1500	4.2	1
KPL603438	Lithium ion (Pouch)	900	4.2	1
L383450	Lithium ion	720	4.2	1
PL223255	Lithium ion	350	4.2	1
PL302030	Lithium ion	120	4.2	1
PL302035	Lithium ion	180	4.2	1
PL304665	Lithium ion	900	4.2	1
PL351230	Lithium ion	90	4.2	1
PL353442	Lithium ion	450	4.2	1

PL385072	Lithium ion	980	4.2	4
PL401225	Lithium ion	80	4.2	1
PL401230	Lithium ion	100	4.2	1
PL401834	Lithium ion	200	4.2	1
PL402025	Lithium ion	140	4.23	1
PL402030	Lithium ion	150	4.2	1
PL402248	Lithium ion	300	4.2	1
PL402535	Lithium ion	300	4.2	1
PL403040	Lithium ion	430	4.23	1
PL403048	Lithium ion	540	4.2	1
PL403436	Lithium ion	450	4.2	1
PL403450	Lithium ion	680	4.23	1
PL405280	Lithium ion	1260	4.2	4
PL405560	Lithium ion	1350	4.2	1
PL414469	Lithium ion	1300	4.2	1
PL425085	Lithium ion	1850	4.2	1
PL454950	Lithium ion	700	4.2	1
PL456066	Lithium ion	1900	4.2	1
PL462079	Lithium ion	800	4.2	1
PL483756	Lithium ion	1100	4.2	1
PL501250	Lithium ion	260	4.2	1
PL503070	Lithium ion	1100	4.2	1
PL503447	Lithium ion	750	4.2	1
PL503562	Lithium ion	700	4.2	1
PL505080	Lithium ion	1000	4.2	1
PL533446	Lithium ion	820	4.2	1
PL551417	Lithium ion	65	4.2	1
PL552045	Lithium ion	470	4.2	1
PL584060	Lithium ion	1450	4.2	1
PL584854	Lithium ion	1600	4.2	1
PL603450	Lithium ion	1100	4.2	1
PL6035135	Lithium ion	1500	4.2	4
PL603960	Lithium ion	1050	4.2	4

PL605280	Lithium ion	1100	4.2	4
PL623048	Lithium ion	800	4.2	1
PL654795	Lithium ion	1500	4.2	1
PL6750115	Lithium ion	2250	4.2	1
PL681730	Lithium ion	280	4.2	1
PL681936	Lithium ion	400	4.2	1
PL701834	Lithium ion	380	4.2	1
PL703496	Lithium ion	1150	4.2	4
PL703675	Lithium ion	1400	4.2	4
PL705280	Lithium ion	1600	4.2	4
PL724656	Lithium ion	1000	4.2	1
PL754666	Lithium ion	1100	4.2	1
PL803048	Lithium ion	1200	4.2	1
PL823458	Lithium ion	1750	4.2	1
PL854983	Lithium ion	2000	4.2	1
PL855085	Lithium ion	2000	4.2	1
PL9045145	Lithium ion	3150	4.2	1
PL904570	Lithium ion	1500	4.2	4
PL9050115	Lithium ion	2650	4.2	1

[d] These cells and batteries are rechargeable. The circuitry containing these cells or batteries is to contain protective components intended to protect the cells or batteries from currents in excess of the maximum charging current and voltage indicated.

[e] The Max Charging Voltage noted in the column is the maximum voltage employed during the abnormal charging test of the secondary lithium ion cell. However, the maximum recommended charging voltage for lithium ion cells is 4.2 V, unless indicated otherwise.

[f] Test Compliance - The cells comply with the tests in UL 1642 as noted:

- 1 - Complies with all single-cell tests
- 2 - Complies with all single-cell tests except the impact test
- 3 - Complies with all single-cell tests except the projectile test
- 4 - Complies with all single-cell tests except the crush test

Marking: Company name, Recognized Component Mark,  on the cell or smallest shipping package containing the cell.

Last Updated on 2020-04-29

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"